

CR-10S Pro V2



Creality CR-10S Pro V2 3D Printer | 300*300*400mm | Upgradable CR-10S Pro | BL touch (Auto-Leveling) | Imported Teflon Tube | Double gear extrusion for smoothly feeding | HD touch Screen.

CR-10S Pro V2

Creality CR-10S Pro V2 3D Printer Advantages

BL-touch Included: Matrix Automatic Leveling, quality Bill Touch automatic leveling device. And the Creality CR-10 Pro V2 3d printer will automatically measure the height of 9 unique points on the heated bed to determine the ideal settings for perfect prints every time.

Filament Sensor: Creality CR-10S Pro V2 3d printer has a newly-added innovative material shortage detection switch, Even also highly sensitive to detect transparent materials.

Stable and high precision motherboard: Creality CR-10S Pro V2 adopts V2.4.1 motherboard independently developed stable performance TMC ultra-quiet drive 256 subdivision for finer printing.

Digital HD Touch Screen Designed:Creality CR-10S Pro V2 comes with Digital HD Touch Screen, large viewing angles, printing status, functions, and parameter settings are clearly displayed, New Friendly UI, easy to use, and learn.

More Smoothly Printing:With Imported high-temperature resistant blue Teflon tube ensure great printing

CR-10S Pro V2

texture, and Bondtech Gear extrusion Structure has two high-density gear and big extrusion force for smooth feeding.

CR-10S Pro V2

Product parameters

Technology
FDM

Print size
300*300*400mm

Print precision
±0.1mm

Slice thickness
0.1–0.4mm

Working mode
online or TF card offline

Nozzle diameter
standard 0.4mm

Number of extruder
1

File format
STL/OBJ/AMF

Extruder temperature
≤260°C

Heatbed temperature
≤100°C

Slicing software
Cura/Repetier-Host/Simplify3D

Machine power
480W

Print speed
Print speed: ≤180mm/s, normal 30–60mm/s

Print material
PLA, ABS, TPU, wood, copper-containing materials, gradient

Power supply
Power supply: input: 100–240V 5.9A 50/60Hz
output: DC 24V 21A
